

Data Sheet

5.523TECA

FRAME SIZE:

112M2-2

50Hz

Output (kW)	5.5
Rotation Speed (rpm)	2920
Voltage	400/690
Full Load Current (A)	10.49 6.06
Full Load Torque (Nm)	17.9880137

60Hz

Output (kW)	6.6
Rotation Speed (rpm)	3504
Voltage	480 828
Full Load Current (A)	10.49 6.06
Full Load Torque (Nm)	14.99

Efficiency Data

100%	75%	50%
87	87.3	86.1

Factory Reference	T2A 112M2-2
Tst/Tn (times)	3.4
Tmax/Tn	4.1
Noise (dB)	78
Moment of inertia	0.008056741
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	2 - M25× 1.5
Paint Colour	RAL 7024
Efficiency	IE2
Bearing (DE)	6306 2RS C3

Power Factor (cos)	0.87
Tmin/Tn	2.8
Ist/In (Times)	10.2
Net Weight (Kg)	32.5
Housing material	Aluminum
Insulation Class	F
Thermal Protection	PTC 130°C
Duty Cycle	S1
Cooling	IC411
Ambient Temperature	-20°C to +40°
Bearing Brand	NSK
Bearing (NDE)	6206 2RS C3

Motors designed and manufactured in accordance with:

IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)

Data Sheet

5.523TECA

Electrotech Drives
1A Washingbay Road
Coalisland, Dungannon
Co Tyrone, BT714ND
Tel: 028 877 29881

Email: sales@electrotechdrives.co.uk