

1.121TPC – IE2

Data Sheet

Electrotech Drives
89 Ballynakilly Road
Dungannon
Co Tyrone, BT716HD
Tel: 028 877 29881
Email: sales@electrotechdrives.co.uk

Model

MY2 802-2

Housing material		Aluminum
Phase		Single
Frame size		80
Power	kW	1.10
Current(A)230V	(A)	6.07
Speed(50Hz)	(r/min)	2830
Efficiency	IE2	
	Eff.100%	79.6
	Eff.75%	78.6
	Eff.50%	72.3
Power factor cosφ	100% load	0.99
Run Capacitor	μf/V	35uf/450V
Start Capacitor	μf/V	--
Cooling		IC 411
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	3.71
Tst/Tn (Times)	0.38
Tmax/Tn (Times)	1.80
Ist/In (Times)	4.90
LRC Code	E
Bearings type(DE)	6204-2RZ
Bearings type(NDE)	6204-2RZ
Oil seals(DE)	20x34x7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Noise dB(A)	78
Net weight(kg)	11.31
Moment of inertia (kg*m ²)	0.001112618