

## ODE-3-120023-1F12

### Input Ratings

|                             |          |
|-----------------------------|----------|
| Supply Voltage              | 200-240V |
| Input Phases                | 1        |
| Supply Current Continuous   | 3.7 Amps |
| Supply Fuse or MCB (Type B) | 10 Amps  |

### Output Ratings

|                     |                    |
|---------------------|--------------------|
| Motor Output Rating | 0.37 kW            |
| Output Voltage      | 0 – Supply Voltage |
| Output Current      | 2.3 Amps           |

### Cable Information

|                        |                   |
|------------------------|-------------------|
| Max Supply Cable Size  | 8 mm <sup>2</sup> |
| Max Motor Cable Size   | 8 mm <sup>2</sup> |
| Max motor cable length | 100 metres        |

### VFD Factory Build Options

|                  |                              |
|------------------|------------------------------|
| EMC Filter       | Internal EMC Filter          |
| Brake Transistor | No Internal Brake Transistor |
| Enclosure        | IP20                         |

### Installation Options & Peripherals

- ▶ Communication Interfaces
- ▶ EMC Filters
- ▶ I/O Options
- ▶ Input Chokes
- ▶ Optistick Smart
- ▶ Output Filters
- ▶ Remote Keypads
- ▶ RJ45 Accessories
- ▶ USB PC Connection Kit



### Dimensions



|         |        |
|---------|--------|
| Size    | 1      |
| Height  | 173mm  |
| Width   | 83mm   |
| Depth   | 123mm  |
| Weight  | 1Kg    |
| Fixings | 4 x M5 |

