

Data Sheet

4.023TECAB3-100-IE2

MOTOR PART CODE:

4.023TECAB3-100-IE2

FRAME SIZE:

100L2-2

50Hz	
Output (kW)	4
Rotation Speed (rpm)	2910
Voltage	400/690
Full Load Current (A)	7.73 4.47
Full Load Torque (Nm)	13.12714777

60Hz	
Output (kW)	4.8
Rotation Speed (rpm)	3492
Voltage	480 828
Full Load Current (A)	7.73 4.47
Full Load Torque (Nm)	10.94

Efficiency Data

100%	75%	50%
85.8	86	84.7

Factory Reference	T2A 100L2-2
Tst/Tn (times)	3.7
Tmax/Tn	4.2
Noise (dB)	77
Moment of inertia	0.005196785
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	2 - M20 x 1.5
Paint Colour	RAL 7024
Efficiency	IE2
Bearing (DE)	6206 2RS C3

Power Factor (cos)	0.87
Tmin/Tn	3.8
Ist/In (Times)	9.9
Net Weight (Kg)	25.8
Housing material	Aluminum
Insulation Class	F
Thermal Protection	PTC 130°C
Duty Cycle	S1
Cooling	IC411
Ambient Temperature	-20°C to +40°
Bearing Brand	NSK
Bearing (NDE)	6206 2RS C3

Motors designed and manufactured in accordance with:

IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)